

Bearing No.	Boundary dimensions (mm)					Basic load rating(kN)		Limiting speeds (rpm)		Weight(Kg)
	基本尺寸					额定负荷		极限转速		
型号	d	D	B	$r_{s\ min}$	$r_{s1\ min}$	Dynamic (Cr)	Static (Cor)	Grease	Oil	重量
				$r_{s\ 最小}$	$r_{s1\ 最小}$	动载	静载	脂	油	
NU204E	20	47	14	1	0.6	25.7	22.6	15,000	18,000	0.122
NU205E	25	52	15	1	0.6	29.3	27.7	13,000	15,000	0.151
NU206E	30	62	16	1	0.6	39	37.5	11,000	13,000	0.226
NU207E	35	72	17	1.1	0.6	50.5	50	9,500	11,000	0.327
NU208	40	80	18	1.1	1.1	43.5	43	9,400	11,000	0.378
NU208E	40	80	18	1.1	1.1	55.5	55.5	8,500	10,000	0.426
NU209	45	85	19	1.1	1.1	46	47	8,400	9,900	0.432
NU209E	45	85	19	1.1	1.1	63	66.5	7,600	9,000	0.495
NU210	50	90	20	1.1	1.1	48	51	7,600	9,000	0.47
NU210E	50	90	20	1.1	1.1	66	72	6,900	8,100	0.54
NU211	55	100	21	1.5	1.1	58	62.5	6,900	8,200	0.638
NU211E	55	100	21	1.5	1.1	82.5	93	6,300	7,400	0.718
NU212	60	110	22	1.5	1.5	68.5	75	6,400	7,600	0.818
NU212E	60	110	22	1.5	1.5	97.5	107	5,800	6,800	0.923
NU213	65	120	23	1.5	1.5	84	94.5	5,900	7,000	1.02
NU213E	65	120	23	1.5	1.5	108	119	5,400	6,300	1.21
NU214	70	125	24	1.5	1.5	83.5	95	5,500	6,500	1.12
NU214E	70	125	24	1.5	1.5	119	137	5,000	5,900	1.3
NU215	75	130	25	1.5	1.5	96.5	111	5,100	6,000	1.23
NU215E	75	130	25	1.5	1.5	130	156	4,700	5,500	1.41
NU216	80	140	26	2	2	106	122	4,800	5,700	1.5
NU216E	80	140	26	2	2	139	167	4,400	5,100	1.67
NU217	85	150	28	2	2	120	140	4,500	5,300	1.87
NU217E	85	150	28	2	2	167	199	4,100	4,800	2.11
NU218	90	160	30	2	2	152	178	4,300	5,000	2.3
NU218E	90	160	30	2	2	182	217	3,900	4,600	2.44
NU219	95	170	32	2.1	2.1	166	195	4,000	4,700	2.78
NU219E	95	170	32	2.1	2.1	220	265	3,600	4,300	3.02
NU220	100	180	34	2.1	2.1	183	217	3,800	4,500	3.33
NU220E	100	180	34	2.1	2.1	249	305	3,500	4,100	3.66
NU221	105	190	36	2.1	2.1	201	241	3,600	4,300	3.95
NU222	110	200	38	2.1	2.1	240	290	3,400	4,000	4.63
NU224	120	215	40	2.1	2.1	260	320	3,200	3,700	5.57
NU224E	120	215	40	2.1	2.1	335	420	2,900	3,400	5.97
NU226	130	230	40	3	3	270	340	2,900	3,400	6.3
NU226E	130	230	40	3	3	365	455	2,600	3,100	6.9
NU228	140	250	42	3	3	310	400	2,700	3,100	7.88

<b>NU228E</b>	140	250	42	3	3	395	515	2,400	2,800	8.73
<b>NU230</b>	150	270	45	3	3	345	435	2,500	2,900	9.92
<b>NU230E</b>	150	270	45	3	3	450	595	2,200	2,600	11